

TECHNICAL SPECIFICATIONS SHEET

BIP

FEATURES

EASYCHAIRS & SOFAS

SEATS & BACKRESTS

CONSTRUCTION	Metalic structure covered in shaped polyurethane foam 55 mm thick (seat) and 40-55 mm thick (backrest), density 75 kg/m3 Fabric covering (see shade card) Black topstitching (white on black backgrounds)
--------------	---



LEGS

SLED	Steel wire frame base Ø 16 mm Leg finish: chromed or lacquered mat black RAL9005 (epoxy powder painted finish) Legs fitted with 4 black ABS anti-slip glides Available in easy chair and 2 seat sofa versions Fixed structure
4 WOODEN LEGS	Structure comprising 4 solid ash wood legs with a natural varnish coating, 4 built-in chromed metal linking pieces Legs fitted with 4 black ABS anti-slip glides Fixed structure
SPIDER LEG BASE	Chromed tubular steel structure Ø 20 mm Legs fitted with 4 black ABS anti-slip glides Fixed structure
CENTRAL STEM FIXED POINT RETURN	Chromed central stem tubular steel structure Ø 50 mm, on circular base Ø 480 mm 360° rotating structure with fixed point automatic return
CENTRAL CRUCIFORM BASE	Polished tubular aluminium Ø 45 mm, central stem cruciform mounted on Ø 700 mm base plate Legs fitted with 4 black ABS anti-slip glides Rotating structure
CASTOR MOUNTED 5-POINT STAR BASE	Chromed steel central stem with 5-point star base mounted on black ABS castors Ø 50 mm Self-braking castors Central stem gas lift mechanism, black finish Adjustment lever - 100 mm adjustment range Base plate Ø 720 mm Castor type: choice of hard floor or soft floor castors Rotating and height-adjustable structure



OPTIONS FOR EASY CHAIRS

CUSHION PAD	Compatible with single seat easy chairs Polyester foam 20 mm thick, density 35 kg/m3 Fabric covering (see shade card)
-------------	---



FOOTSTOOL

CONSTRUCTION	Mixed hardwood and fibre board structure covered in shaped polyurethane foam 70 mm thick, density 65 kg/m3 Fabric covering (see shade card) Black topstitching (white on black backgrounds) ABS glides Built-in linking pieces allow the connecting of the footstools
--------------	---



LOW TABLE

WORKTOP	Frosted glass 10 mm thick
LEGS	> Wire frame: Steel wire frame base Ø 12 mm Leg finish: chromed or lacquered mat black ((epoxy powder painted finish) Legs fitted with 4 black ABS glides Secured to worktop using 4 metal linking pieces > Wood: Structure comprising 4 solid ash wood legs with a natural varnish coating, 4 built-in chromed metal linking pieces Legs fitted with 4 black ABS glides

DIMENSIONS & WEIGHT

OVERALL DIMENSIONS (in mm)							
EASYCHAIRS & SOFAS							
	SLED		4 WOODEN LEGS	SPIDER LEG BASE	CENTRAL STEM FIXED POINT RETURN	CENTRAL CRUCIFORM BASE	CASTOR MOUNTED 5-POINT STAR BASE
Structure	Fixed		Fixed	Fixed	Rotating with fixed point automatic return	Rotating	Rotating and height- adjustable
Width	670	1170	670	670	670	670	720
Depth	620		600	600	600	600	660
Height	850		870	860	860	860	810 / 910
USEFUL DIMENSIONS (in mm)							
Seat width	430	940	430	430	430	430	430
Seat depth	460		460	460	460	460	460
Seat height	440		460	450	450	450	390 / 490
WEIGHT (kg)							
Net weight	10,5	17	9,5	10,5	23	11,5	13
Max. load	110	230	110	110	110	110	110

COMPLEMENTARY ITEMS				
	FOOTSTOOL	LOW TABLE ON 4 WOODEN LEGS	LOW TABLE ON WIRE FRAME BASE	CUSHION PAD
OVERALL DIMENSIONS (in mm)				
Width	410	Ø 600	Ø 600	430
Depth	410			460
Height	410	450	450	37
WEIGHT (kg)				
Net weight	7,5	-	-	-
Max. load	110	50	50	-

Guarantee
5
YEARS

Manufactured
to
ISO
14001

Manufactured
to
ISO
9001

