

SOLANGE

FEATURES

DESKTOP & PARTITION SCREENS

DESKTOP SCREENS

COMPOSITION	Acoustic partition screen construction: > Outer frame made from aluminium 47 mm thick, joined by 4 rounded ABS corner pieces > Core made from honeycomb cardboard 25 mm thick (made from 100% recycled fibres), clad with 1 layer of 10 mm thick acoustic polyester fibre on each panel face > This polyester fibre offers the following environmental benefits: > Oeko tex certified foam - certification guaranteeing the absence of substances posing a health risk > Manufactured using a minimum of 85% recycled fibres > 100% recyclable > Fire-resistant foam classed B-s1.d0 (Euroclasses according to EN 13501-1 equivalent to M1 fire rating) > Fabric covering (see fabrics shade card) > Panel with drilled openings on each side of the upper section to receive 4 screw-on ABS knobs Ø 25 mm (White or Graphite grey finish depending on the clamp colour), supplied with fixing clamps > Tackable panel SOLANGE acoustic desktop screens absorb +/- 50% of nuisance noise Acoustic performance report produced by CEDIA Liège can be provided - Contact us for details
SECURING METHOD TO WORKTOP	The inclusion of fixing clamps is essential in order to hold the panels securely in place and are positioned at the extremities of each panel (distance between the external edge of the panel and the clamp: 95 mm) > Clamps made from 6 mm thick sheet steel crowned by a Ø 16 mm metal ring to raise the desktop screen from the worktop surface by 20 mm > Lacquered epoxy finish. > Choice of 3 colours available (see shade card) > Compatible with partition screens from 19 mm to 30 mm in thickness > Secure to the worktop using threaded clamps, wood screws (affixed at the extremities) or a simple shaft (lateral version) Fixing clamp models vary according to the chosen configuration (see Pricing Guide) > Standard individual clamps for frontal or lateral attachment (affixed at the extremities) on screens H. 400 mm > Standard individual clamps for frontal attachment on screens H. 700 mm > Double fixing clamps for frontal or lateral attachment (starter/add-on desks) on screens H. 400 mm > Bolt-through clamps on screens H. 400 mm for single worktop shared workstations
INFORMATION ON DIMENSIONS (see table below)	Features > Panels measure 22 mm less than the width of the worktop (e.g.: 1,578 mm with a worktop W. 1,600 mm) > Height of the screen panel alone: H. 380 mm excluding fixing clamps/ Height to the top of the worktop surface H. 400 mm > Panel thickness: 47 mm, overall thickness including knobs: 68 mm In the Bench starter/add-on version, the space between 2 front facing panels is 22 mm, allowing for the inclusion of a lateral desktop screen D. 800 mm in the layout. For the bolt-through clamp version on single worktop shared workstations, there are 2 choices of desktop screen panel available: > option 1: choose a panel with the same width as the worktop (e.g.: 1,578 mm with a worktop W. 1,600 mm) > option 2: choose a panel 400 mm shorter than the worktop width, to allow the inclusion of a desk lamp or a flat-screen monitor arm on either side of the desktop screen (e.g.: 1,178 mm with a worktop W.1,600 mm)

OPTIONS FOR DESKTOP SCREENS

RAIL	> Sheet steel 6 mm thick, H. 50 mm, with drilled openings at the extremities, to accommodate the insertion of connector knobs that screw directly into the panel > Grooved rail built into the central section of the panel to fit accessories > Lacquered epoxy finish (see metal shade card)
ACCESSORIES	> Sheet steel 1 mm thick, with drilled openings in the upper section to receive ABS knobs and an accessories rail > Each accessory is supplied with 4 ABS knobs (2 white and 2 graphite grey) > Lacquered epoxy finish (see metal shade card)

PARTITION SCREENS

COMPOSITION	Several partition screen versions available: standard or acoustic, fabric covered or part-fabric/part-glazed. Standard partition screen construction: > Outer frame made from aluminium 47 mm thick, joined by 4 rounded ABS corner pieces > Self-supporting partition screen without structural core, no acoustic absorption properties > Fabric covered (see fabrics shade card) Acoustic partition screen construction: > Outer frame made from aluminium 47 mm thick, joined by 4 rounded ABS corner pieces > Core made from honeycomb cardboard 25 mm thick clad with 1 layer of 10 mm thick acoustic polyester fibre on each panel face > This polyester fibre offers the following environmental benefits: > Oeko tex certified foam - certification guaranteeing the absence of substances posing a health risk > Manufactured using a minimum of 85% recycled fibres > 100% recyclable > Fire-resistant foam classed B-s1.d0 (Euroclasses according to EN 13501-1 equivalent to M1 fire rating) > Fabric covering (see fabrics shade card) Part-fabric/part-glazed partition screen (standard and acoustic) construction: > Same as fabric covered partition described hereabove (in both standard and acoustic versions) combined with a transparent PMMA panel 6 mm thick H. 385 mm, affixed using metal bridging clamps integrated into the partition 15 mm spacing between the fabric covered panel and the PMMA panel > Epoxy lacquered clamps available in 3 choices of colour (see shade card) Each partition screen features perforations at all 4 extremities on each side, to receive 8 ABS screw-on knobs Ø 25mm (White or Graphite grey finish depending on the foot colour), supplied with the feet These screw-on knobs are designed to link the partition screens to one another, using a connector kit sold separately (see options)
-------------	---

LEGS

STABILISER FEET	> Stabiliser feet made from 6 mm thick sheet steel, crowned by a Ø 16 mm metal ring to raise the partition screen from the ground by 22 mm (fixed feet). The castor-mounted version is raised by 85 mm from the ground. > Lacquered epoxy finish. Choice of 3 colours available (see shade card) Different foot models available depending on chosen configuration > Stabiliser feet for individual partitions: 2 oblong feet W. 400 x D. 70 mm > Stabiliser feet for multiple partition configurations: 1 oblong foot W. 400 x D. 70 mm and one circular foot Ø 70 mm > Castor-mounted feet: 2 oblong base plates W. 400 x D. 70 mm mounted on 4 ABS castors Ø 55 mm (2 with brakes), in a black finish
-----------------	--

LINKING SYSTEM

COMPOSITION	> Elasticated fabric linking system, comprises 8 black connectors (W. 55 x H. 32 mm), each featuring a metal hook in a black lacquered epoxy finish > Facilitates the linking of 2, 3 or 4 partition screens, either configured in line or in variable angle layouts, connecting with the screw-on knobs located on the upper and lower sections of the partitions > Supplied in packs of 2 units It is not possible to link: > 2 partition screens of different heights > 1 fabric covered screen and 1 part-fabric/part glazed screen
-------------	--

OPTIONS FOR PARTITION SCREENS

ACCESSORIES	Whiteboard with pen tray > White PMMA whiteboard 6 mm thick, W. 700 x H. 585 mm > Fitted with a metal pen tray, sheet steel 1 mm thick, W. 190 x H. 85 mm x D. 80 mm, epoxy lacquered finish, available in multiple colours (see shade card) > Attaches to the partition screen using metal fixing clamps, in a matching finish to pen tray
-------------	---

DIMENSIONS

DESKTOP SCREENS		
ACOUSTIC DESKTOP SCREENS		
OVERALL DIMENSIONS (in mm)		
Height	380	700
Width	778 / 978 / 1,178 / 1,378 / 1,578 / 1,778	1,178 / 1,378 / 1,578 / 1,778
Thickness	47	
USEFUL DIMENSIONS OF PARTITION SCREEN (in mm)* / Knobs and clamps included		
Height	400	400 above the worktop 300 below the worktop
Width	778 / 978 / 1,178 / 1,378 / 1,578 / 1,778	1,178 / 1,378 / 1,578 / 1,778
Thickness	68	
WEIGHT (kg)		
Max load (kg)	7	7

* Measurement taken between the worktop surface and the top of the desktop screen

ACCESSORIES RAILS	
OVERALL DIMENSIONS (in mm)	
Height	50
Width	670 / 870 / 1,070 / 1,270 / 1,470 / 1,670
Thickness	6
WEIGHT (kg)	
Max load (kg)	7

ACCESSORIES FOR DESKTOP SCREENS						
	Letter tray starter unit	Letter tray add-on unit	Pen tray	Shelving	Planter with 3 compartments	Magnetic whiteboard
OVERALL DIMENSIONS (in mm)						
Height	60	65	75	170	185	275
Width	335		225	450	327	275
Depth/Thickness	255		120	190	129	1
WEIGHT (kg)						
Max load (kg)	1,5	1,5	1	1,5	1,5	0,5

PARTITION SCREENS				
STANDARD AND ACOUSTIC PARTITION SCREENS				
	Fabric covered partition screens			Part-fabric and part-glazed partition screens
OVERALL DIMENSIONS (in mm)				
Height	1178	1578	1778	1578
Width	800 / 1,200			800 / 1,200
Thickness	47			6 / 47

	Fabric covered partition screens			Part-fabric and part-glazed partition screens
USEFUL DIMENSIONS OF PARTITION SCREEN (in mm)* / Knobs and feet included				
Height (fixed legs)	1200	1600	1800	1600
Height (castor-mounted stabiliser feet)	1263	1663	1863	1663
Width	800 / 1,200			800 / 1,200
Thickness	68			

ACCESSORIES FOR PARTITION SCREENS	
	Whiteboard with pen tray
OVERALL DIMENSIONS (in mm)	
Height	703
Width	700
Depth	148
WEIGHT (kg)	
Max load (kg)	1

