

GRETA - Bench

PROPERTIES

GENERAL	Melamine-covered particle boards, thickness 25 mm or 19 mm. 2 faces treated with anti-reflective hue Density of panels 650kg/m3 Flat edges with ABS stuck on thickness 2mm, chamfered top and bottom. Edges matched to the worktop hue Boards originating from sustainably-managed forests (PEFC). Fire classification M3 (average flammable combustible) in accordance with standard NF EN 13501-1 Boards certified E1 (control of formaldehyde emissions) with 6.5mg HCNO/ 100 mg and compliant with standard NF EN 717-2.
WORKTOPS AND UPPER SHELVES	Melamine boards 25 mm thick Worktops with scalloped edges (D 225 mm) for positioning screens (up to 21 inches). Screen support shelf of white melamine positioned under the main work surface (useful height: 470 mm), predrilled for 2 cable ports ø 80 mm. STK finish: light oak RI SDM finishes: snow white MG, cashmere grey M6, Brunswick oak R3, amber walnut RL, coffee oak M9
LEGS	Melamine boards thickness 19 mm. End leg D. 630 mm, covered in a side panel D. 800 mm to close a configuration Middle leg D. 490 mm to facilitate circulation between 2 modules, drilled for passing cables. Legs fitted with adjustment stabilisers (travel 15 mm) STK finish: snow white
SIDE PANEL	Melamine boards thickness 19 mm. Is fastened by insert onto left and right end feet. For independent modules, 2 asymmetric side panels: one long (H: 1128 mm) and one short (H: 866 mm) to be positioned on the left or right as chosen For left or right end modules, only the long side panel (H: 1128 mm) Finishes: coordinated with the worktop
FACE MODESTY PANEL	Melamine boards thickness 19 mm. STK finish: snow white




PROPERTIES

OPTIONS

Reception panel 	Melamine boards thickness 19 mm. W.645 x H 841 mm > Is fastened under the reception shelf by interlocking > Fitted with a bag carrying shelf (W485xD135 mm) positionable on the left or right of the reception panel > Finishes: see shade card for worktops - bag carrying shelf
LED Kit	LED kit to be positioned behind the reception panel (fastening on both sides) There is a UK and CH version with adaptor White LED kit: > White light > Switch on user side Colour LED kit: > Colour lights are either fixed or changing > Operates with remote control


DIMENSIONS

OVERALL DIMENSIONS (in mm)

	RECTANGULAR		ANGLES
High standard modules			
Type of module	Free-standing, L and R end, middle	Free-standing	Free-standing, L and R end, middle
Overall depth	860		880
Depth of worktop with scalloped edge	565		
Overall (useful) width	1238 (1178)/1438 (1378) / 1638 (1578)	1638/ (1578)	1670 (1578)
Desk height	735	950	735
Total height	1130		
Useful height of screen support shelf / counter top unit	470		



DIMENSIONS

	SITTING / STANDING	SITTING	
DDA modules			
Type of module	Free-standing, L and R end	Middle	
Overall depth	1110 / 860	1000	
Depth of worktop with scalloped edge	565	-	
Overall (useful) width	1710 (1690)	800	
Desk height	735 / 1135	735	
Useful height of screen support shelf / counter top unit	470	-	



GRETA - Storage Units

PROPERTIES

GENERAL	Unit Supplied Assembled Melamine-covered particle boards, thickness 25 mm or 19 mm. 2 faces treated with anti-reflective hue Density of panels 650 kg/m3 Flat edges with ABS stuck on thickness 2mm, chamfered top and bottom. Edges matched to the worktop hue Boards originating from sustainably-managed forests (PEFC). Fire classification M3 (average flammable combustible) in accordance with standard NF EN 13501-1 Boards certified E1 (control of formaldehyde emissions) with 6.5mg HCNO/ 100 mg and compliant with standard NF EN 717-2. Melamine boards (except for Brunswick oak hue R3 and coffee oak M9) compliant with standard ISO22196 which give them anti-bacterial properties.
---------	---

CABINETS

SIDE BACK BASE	Melamine boards thickness 19 mm Base and back scalloped edge to allow passing of cables Base fitted with stabilisers screwed into inserts (Adjustment travel 15mm) Median vertical separation fixed at W1200. Supplied with 1, 2 or 3 shelves W600 D400. Space at the back of the unit to allow passing of cables. Uniformly distributed useful space: 50 kg STK finish: snow white MG
SLIDING DOORS	Melamine boards thickness 19 mm Rail: ABS rail with roller. End of travel stop + 2 plastic (low noise) stops Lock: Cylinder lock with 2 keys (of which 1 folding). Closure on the left side part or the middle partition. Handle: Handled profiled in wired metal over the entire left height of the door. STK finish: light oak RI SDM finishes: snow white MG, cashmere grey M6, Brunswick oak R3, amber walnut RL, coffee oak M9
FINISH TOP	Melamine boards thickness 25 mm Pre-drilled boards for 2 cable ports ø 80 mm STK finish: light oak RI SDM finishes: snow white MG, cashmere grey M6, Brunswick oak R3, amber walnut RL, coffee oak M9



PROPERTIES

CABINETS - OPTIONS


Additional shelf	Melamine boards thickness 25 mm W.565 xD. 365 mm > Is fastened with cleats on adjustment levels spaced 30 mm apart STK finish: white MG
Drawer unit	Face: Melamine boards thickness 19 mm Body: metal structure W.565xD.335xH.350 mm Push closing system - Slides on rollers Interior organisation: partition positionable on the left or right for A4 (or foolscap) suspended files + small storage area (W.200 mm) Face - STK finish: light oak RI Face - SDM finishes: snow white MG, cashmere grey M6, Brunswick oak R3, amber walnut RL, coffee oak M9 Body: STK finish: white SO

SHELVING

Shelving To be fitted or fixed (by the customer)	Melamine boards thickness 19 mm Metal frame: square tube section 20x20 mm W.1200 xD. 400x H. 400 mm Is positioned on the bench or fastened to the wall (by the customer) using wall plugs Melamine shelves - SDM finishes: snow white MG, cashmere grey M6, Brunswick oak R3, amber walnut RL, coffee oak M9, light oak RI Metal frame - SDM finish: white SO
--	---

DIMENSIONS

OVERALL DIMENSIONS (in mm)

Cabinets					
Depth	430	430			
Height	1135	735			
Width	1200	1200		600	
Shelving					
Depth	400				
Width	1200				
Height	400				

