

TECHNICAL SHEET


MODULO

CHARACTERISTICS

WORKTOPS

MELAMINE	> Melamine covered particle board panels, 38 mm or 30 mm thick. 2 sides treated with an anti-reflective coating Panel density 650kg/m³ Bonded ABS edge banding, 2 mm thick, rounded on upper and lower edges. Edge banding to match worktop finish Panels sourced from sustainably managed forests (PEFC). Fire rating M3 (combustible, moderately flammable) in accordance with the standard NF EN 13501-1 Panels are certified E1 (control of formaldehyde emissions), emitting 6.5 mg HCNO/100 mg and compliant with standard NF EN 717-2 Melamine panels (except Brunswick oak R3 and Coffee oak M9) comply with the standard ISO 22196 for antibacterial properties. > Reinforcement beams for 90° corner angle worktops D. 1350 mm and rectangular worktops L. 1800 mm > Option for worktops pre-cut for top-access housings (rectangular and curved worktops only) Top-access housings to be ordered separately (see Options below) - Metal cable trough included.
----------	---

LEGS AND STRUCTURE

MELAMINE PANEL 	> Melamine panel leg 38 mm or 30 mm thick, matching worktop Shared or independent leg, depending on the configuration selected Assembly on metal inserts 3 leg types: symmetrical, asymmetrical or angled Legs with adjustable stabiliser feet, adjustable through 15 mm.
METAL 	> Circular section legs in tubular steel ø 70 mm > Square section legs in tubular steel 60 x 60 mm > Shared or independent leg, depending on the configuration selected > Lower part with chromed end housing the adjustment mechanism > Adjustable stabiliser in translucent ABS. Adjustment through 20 mm. > Upper plate in sheet steel with brace





CHARACTERISTICS

OPTIONS

 WORKTOP POWER & CABLE MANAGEMENT 	Square cable port for direct connectivity: > Cable port in ABS with retractable top-access housing for direct connectivity on the worktop. > Dimensions: L 124 x D 90 mm. Clearance 82.5 mm under the worktop. > Fitted with 1 EUR PC power feed + 1 RJ 45 and 1 USB charger or HDMI power feed. Cables supplied. UK version available. > Assembly: For installation on the worktops (provide a Ø 80 mm opening for cable port) > Finishes: White SO or Black OF Top-access housings with and without feed: > Top-access housing with soft closing mechanism, fitted with grey brushes. > Assembly: For installation on worktops pre-cut for top-access housing. Dimensions: L 240 x 120 mm > Version with integrated fixed feed (2 PC + 2 RJ45 + 1 USB charger or 1 HDMI socket). Provided with 2m EUR power cable. CH and UK versions available. > Finishes: Natural aluminium OI or epoxy White SO.
CENTRAL TOP-ACCESS HOUSINGS AND CABLE TROUGHS FOR ELLIPTICAL TABLES 	Elliptical tables can be fitted with central cable troughs with top access housing in metal or Altuglas® finish. These top-access housings have slots for the passage of cables and adapt to the worktop thickness by means of adjustable supports.
MODESTY BOARD 	Sheet steel thickness 0.7 mm, with three horizontal grooves. Finish to match the finish of the legs. 2 vertical braces are welded to the inner face. Secures with 2 metric screws M6x12 on inserts positioned beneath the melamine worktop. Total overall height beneath the worktop: H. 280 mm - For worktop L 1800: mm: L 1670 mm - For worktop L 1400 mm (rectangular and curved): L 1270 mm - For 90° corner angle worktop L 1350 mm L 505 mm - For trapeziform worktop: L.900 mm (secured using wood screws) Not compatible with worktops fitted for top-access housings



OVERALL DIMENSIONS (in mm)				
RECTANGULAR WORKTOPS			Direction of grain 	
Depth	700	700		
Width	1400	1800		
Fixed leg height	740 / 748	740/748		
CURVED WORKTOPS	SYMMETRICAL 	ASYMMETRICAL L 	ASYMMETRICAL R 	
	Depth	700 / 780	700 / 850	700 / 850
	Width	1400	1400	1400
	Fixed leg height	740 / 748	740 / 748	740 / 748
ANGLES AND ELLIPSE	OPEN ANGLE 	CLOSED ANGLE 	ELLIPSE 	
	Depth	700 / 1350	700	900
	Width	700	700	1400
	Fixed leg height	740 / 748	740/748	740 / 748
CABLE TROUGH KIT	TABLE DIMENSIONS	TOP-ACCESS DIMENSIONS	NUMBER OF CABLE TROUGHS	TOP-ACCESS
	L. 3200 x D. 1560	L. 1278 x D. 155	1 x L. 1400	1 elliptical
	L. 4600 x D. 1700	L. 2673 x D. 298	2 x L. 1400	2 end pieces
	L. 6000 x D. 1700	L. 4071 x D. 298	3 x L. 1400	2 end pieces + 1 central L. 1400
	L. 6400 x D. 1700	L. 4471 x D. 298	1 x L. 1800 + 2 x L. 1400	2 end pieces + 2 central L. 900